





Gateway lite | SF-930EU User Guide for Installation





Table of Contents

Gateway Introduction	2
Wi-Fi specifications:	2
Powering Up the Gateway	3
Installing Gateway - Finding Gateway wifi	3
WiFi configuration	4
Installing gateway – Wi-Fi Configuration	4
Installing gateway – in case of a problem	5

Gateway Introduction

This user guide will walk you through your Salusfin Gateway Lite set up.

Wi-Fi specifications:

- Your Wi-Fi router must support the 802.11N standard to install your Gateway Lite.
- WPA2-PSK should be used.
- Wi-Fi channel not higher than 9.
- 2.4GHz Wi-Fi frequency



Powering Up the Gateway

Power up the gateway by connecting the power supply pin with the holder and gateway lite.

Picture 1 shows the Gateway lite. Picture 2 -The power supply. Picture 3- the Holder.

On powering, make sure the Gateway Lite flashes blue once to indicate that it is powered on.

Place it in the middle of the home to obtain maximum coverage.

The wireless range is usually 30-100 meters, but may vary depending on the building construction.







Gateway Lite SF 930 Eu

Power Supply

Holder

Installing Gateway - Finding Gateway wifi

Check under your Wi-fi settings the list of Wi-fi networks available (Picture 4).

The Gateway Lite will now be listed as NorthQ Gateway XXXX (where XXXX are the last 4 digits of the Q-Stick serial number)

Connect to the Wi-fi network provided by Gateway Lite to configure it. (Picture 5 and 6) It's normal that it will tell "No Internet access" as in Picture 7.

Picture 8, is showing a successful connection to Gateway Lite from computer.





WiFi configuration

Configuration is done through web browser. Web page as in Picture 9 should open.

iOS and Windows Users

- The setup page should appear automatically. Otherwise, open a browser and enter the address http://192.168.0.1

Android Users

- A notification should appear in a couple of seconds asking you to sign in to the network. Click on the notification. Otherwise, open a browser and enter the address<u>http://192.168.0.1</u>

QStick	setup	
INSTA	u	
NQ-930-EU S/N: F/W: 124	NorthQ	

Picture 9

Installing gateway – Wi-Fi Configuration

Choose your router's Wi-fi network. (Picture 10 and 11)

Key in Wi-Fi password/secure key in both fields (Picture 12) and Press Save

You will get installation confirmation (Picture 13) and network will disappear from the list of networks and the device you are using will seek for your home network again.

Navigate in your browser to Salusfin Control Manager in address <u>https://control.salusfin.com</u> (Picture 13, 14) to continue installing components.

In case you experience difficulties please check the next page.

				_		WELCOME TO THE SALUSFIN LOGIN PAGE	
Select your network <u>V</u> Test	ViFi not listed?	Select your network Test WLANo1	WiFi not listed?	Select your network	WiFi not listed?	0 3 4 5	Ľ
Network password	-	Test WLANo1		Network password			T
Confirm network password				Confirm network password		Login to your account	Installation complete
SAVE		SAVE		SAVE		herrik jakobsson 🖷 Persend	Check that the Q-Shick's LED is blue and install your devices on
ВАСК		BACK		BACK		<u>8</u> 5yr h	NQ.430EU NorthQ SN FW:
NQ:930-EU SIN: FW:	NorthQ	NQ-930-EU SiNi FrW-	NorthQ	NQ-990-EU Sint FW:	NorthQ	Beechmoned	
Picture 10		Picture 11	L	Picture 2	12	Picture 13	Picture 14



Installing gateway – in case of a problem

In case the gateway LED is not lit at all, check that is in correct way in the holder.

If the LED is **RED** on the Gateway lite it means that the network configuration failed. Start again by

Unplugging the Gateway lite, press and hold the button while connecting it back to power.

The LED will flash Blue quickly for a while and when LED is dark release the button. (It should take a couple of seconds to turn dark. It starts when the button is pressed).

When the LED is dark you can proceed to the Next phase.







